

## DESCRIPTION

Johnstone's Stormshield Pliolite® Based Masonry Finish is a premium quality, solvent-based paint formulated for exterior use on cement rendering, rough cast, brick and concrete. It provides a smooth matt finish that has excellent adhesion to previously painted and suitably sealed surfaces. The Pliolite resin enables application at temperatures down to -5°C and becomes showerproof in 20 minutes, allowing all year round exterior decoration.

## RECOMMENDED USES



Suitable for exterior use.

## TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash.

## COLOUR RANGE

Tintable to a range of colours available in the Johnstone's Trade Colour Card.

## FINISH

Matt.

## VOLUME SOLID

33%

## COVERAGE



Approximately 6 square metres per litre, depending on the nature and porosity of the surface.

## DRYING TIME\*



Recoat after 16–24 hours under normal drying conditions.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

## CLEANER

White spirit.

## VOC CONTENT

High VOC content 25–50%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/c): 430g/l (2010).  
This product contains max 430g/l VOC.

## FILM THICKNESS

Wet: 125µm, dry: 41µm.

## KEY PROPERTIES

- Over 15 years life expectancy
- Showerproof in 20 minutes allowing all year round application.
- A solvent-borne smooth matt coating for exterior walls.
- Excellent adhesion to previously painted or untreated porous surfaces.

\*Pliolite® is a registered trademark of Eliokem.

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Repair cracks and defective areas and treat fungal or algal growth with Johnstone's Sterilisation Wash as directed. For further advice contact Technical Advisory, on 01924 354354.

## APPLICATION



Stir well. Easy to apply by brush or roller. Seal absorbent surfaces with a coat of Stormshield Stabilising Solution applied as directed. If more than one can of a colour is to be used in the same area, intermix before use.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- FLAMMABLE
- Harmful to aquatic life with long lasting effects.
- Hazardous ingredients: 4,5-dichloro-2-octyl-3(2H)-isothiazolin-3-one.
- Avoid release to the environment.
- Repeated exposure may cause skin dryness or cracking.
- Safety data sheet available on request.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- Wear protective gloves/protective clothing/eye/face protection.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Do not breathe spray. Wear respiratory protection.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.

## SIZES

5 Litre.



The British Board of Agrément is designated by Government to issue European Technical Approvals based on the assessment of products for construction. Johnstone's products carrying this logo have undergone rigorous independent testing and received approval from the BBA.